

Track Tac *Track Treatment*

Track Tac *Track Treatment* is a special organic formulation designed to aid in dirt and clay track preparation. It is based on both vegetable and animal chemistries.

Track Tac *Track Treatment* provides a hard compact surface without the use of Calcium Chloride or Lignin Sulfonate .

Track Tac *Track Treatment* is Calcium free.

Track Tac *Track Treatment* minimizes surface break up through a complete day or night of competition.

Track Tac *Track Treatment* has an extremely low usage level compared to Calcium Chloride.

Track Tac *Track Treatment* is much more economical to use than Calcium Chloride

Track Tac *Track Treatment* is added to the water in the water truck and applied just as water would be applied to the track.

Track Tac *Track Treatment* “is run” in on race day just as water would be “is run” into the track.

Directions for Application

Before using the Track Tac *Track Treatment* the track should verify with local authorities that the application meets local environmental requirements.

Add ¼ to 1 gallon of Track Tac Track Treatment per 500 to 1,000 gallons of water in the track watering truck and apply to the track as if it were just water. An application to the track while the track is turned up is beneficial because it helps get the Track Tac Track Treatment deep into the base soil of the track. Subsequent applications to the track should be with the mix. A film may be visible at this point of the application. The track should be very absorbent when the mix is applied. About 2.5 gallons of Track Tac Track Treatment should be applied to the track per 1/4 mile of track after the initial application. The initial application of Track Tac Track Treatment should be 5 gallons per 1/4 mile of track. Very difficult track may require more Track Tac Track Treatment than listed above. Run in the track as normal. The track will pack down to a uniform compact surface that will remain almost dust free with higher surface integrity through the complete race. The treated water should be applied no more or less frequently than water is normally applied during a complete day or night of racing.

Track Tac *Track Treatment* will allow the track to hold moisture much longer than water alone.

The Information and Recommendations Contained Herein Are to the Best of the Companies Knowledge and Belief, Accurate and Reliable as of the Date Issued. However, it Is the User's Responsibility to Determine the Safety, Toxicity, and Suitability for His Own Used of the Product Described Herein. Since the Actual Use of this Product Is Beyond Our Control, No Guarantee, Expressed or Implied, Is Made by the Company.

ATTL Products, Inc.

216 East Holly Hill Rd. * Thomasville, NC 27360 * 336/474-3500 * Fax 336/475-0100

www.tracktac.com